

TopAir's Downflow Workstation is a standalone ductless unit that protects lab staff from harmful particulate matter or fumes.

The Downflow Workstation features an open structure which enables easy access for lab personnel.

Particles matter flows downward through the polypropylene work surface and contaminants are removed using a HEPA filter.

Structure:

- 8 mm welded polypropylene with high chemical resistance
- Perforated retractable polypropylene worktop (stainless steel optional)

- Manual analog on/off system with fan speed adjustment
- Polypropylene worktop combined with a drawer for easy cleaning
- H14 HEPA filter
- High efficiency EC fan
- 800 lux LED lighting
- Optional: 395 nm UV light (black light)
- **CE certified**



Downflow Unit

| Spec/ Model | DF-60 | DF-90 | DF-120 |
|---|---|---------------------------------------|--|
| External Dimensions WxDxH | 60 x 70 x 120 cm 23.6 x 27.5 x 47.2" | 90 x 70 x 120 cm 35 x 27.5 x 47.2" | 120 x 70 x 120 cm 47.2 x 27.5 x 47.2" |
| WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS | | | |
| Internal Height | 70 cm / 27.5" | 70 cm / 27.5" | 70 cm / 27.5" |
| Power Supply | 115/230 V 50/60 Hz, Single phase | 115/230 V 50/60 Hz, Single phase | 115/230 V 50/60 Hz, Single phase |
| Light | LED 800 lux | LED 800 lux | LED 800 lux |
| Worktop | Polypropylene | Polypropylene | Polypropylene |
| Structure | Polypropylene | Polypropylene | Polypropylene |
| Filter | H14 HEPA | H14 HEPA | H14 HEPA |
| Fan | EC fan | EC fan | EC fan |